



Technical parameter:

Dimensions: 103*48*21(mm)
 Operating Voltage: DC 12V±%10
 Operating Current: <70mA
 Card Reading Distance: 5-10cm
 Ambient Temperature: -25° C to 75° C
 Ambient Humidity: 10%-90%
 Type of Card: EM(ID) card 125KHz,
 MIFARE card 13.56MHz
 Package: 100PCS per carton
 Carton Size: 43.5*56*23(cm)

Wiring Connection:

WG26/34	RS485	RS232
Red: DC 9V-16V	Red: DC 9V-16V	Red: DC 9V-16V
Black: GND	Black: GND	Black: GND
Green: D0	Green: 4R+	Green: RX
White: D1	White: 4R-	White: TX
Blue: LED		
Yellow: BEEP		
Gray: Door Bell		
Purple: Door Bell		

Features and functions:

- Wiegand 26bits/ Wiegand34bits or RS232 Standard Format Data Output
- Less than 0.2 second Response Speed
- Built-in Antenna, Built-in LED (Double Color LED), Built-in Loud Speaker (Buzzer)
- 100 Meters Communication Distance
- Real Time Data Transfer
- PVC Case Material, With Water-Proof Function
- Audiovisual indication: When a registered card is presented to the reader
blue LED flashes green and the beep sounds