

AC-300

Metallic Casing Outdoor Access Control


AC-300, one of the innovative biometric fingerprint readers for access control applications, offers unparalleled performance. It adopts the advanced fingerprint algorithm for reliability, precision and excellent matching speed.

Its metallic casing and IP65 rated protection enables it to resist water, dust and other outside damages.

AC-300 offers the flexibility to be installed standalone or with any third party panels that support 26-bit wiegand. User can be enrolled by the administrator card when the device works in standalone mode. TCP/IP and RS485 are available, so that the device can be connected easily and conveniently.



Features



► **Rugged structure and extra durability**

- * IP65 rated waterproof and dustproof structure



► **Metallic casing**

- * Vandal-proof for outdoor installation



► **Fast and accurate fingerprint algorithm**

- * 1 touch a-second user recognition
- * Stores 1,500 templates, 10,000 cards and 100,000 transactions



► **Easy installation and connectivity**

- * Wiegand input&output
- * Network interfaces for TCP/IP or R485



► **Full access control features**

- * Anti-passback
- * Access control interface for 3rd party electric lock, door sensor, exit button, alarm



► **Easy operation and management**

- * OLED, buzzer, optional integrated smart card reader and external USB keypad
- * Fingerprint and RF card reader for multi-model authentication

Specifications:

Fingerprint Capacity	1,500 templates
ID Card Capacity	10,000
Transaction Capacity	100,000
Hardware Platform	ZEM710
Sensor	SK Optical Sensor
Algorithm Version	SK Finger v10.0
Communication	RS485, TCP/IP, USB-host
Access Control Interfaces for	3 rd party electric lock, door sensor, exit button, alarm
Wiegand Signal	Input & Output
Standard Access Control Function	Time Zone, Group, Multi-identification Duress mode, Anti-passback
Optional Functions	Mifare, external USB keypad
Display	N/A
Power Supply	12V DC
Operating Temperature	-10°C- 60°C
Operating Humidity	10% -90%
Protection Grade	IP65
Dimension(W*H*D)mm	73*148*34.5
Gross Weight	1.15kg

Optional Accessories:



RFID Reader



Exit Button



Electric Lock




Alarm



Door Sensor

Configuration:



Application:



Networked Security:
School



Networked Security:
Building



Standalone Access Control:
Airport



Standalone Access Control:
House



Time Attendance:
Factory



Time Attendance:
Office



Your Trusted Security
Service Provider

Tel: +65 6748 1155

