

CR-TEXT-340

Point of Sale (POS) Video Text Inserter



Key Features

- Displays up to 10 lines
- Displays up to 40 characters per line
- Programmable text sizes, gray scale, background, and transparency
- Text can be positioned anywhere on screen
- Programmable scrolling speed, pause and screen clear timers
- Blinking text and LED on flagged transactions (exceptions)
- 16 programmable flagged transactions
- Up to 4000 transactions and exceptions logging with time stamp (minimum 500, optional)
- 2 trigger inputs
- 2 alarm outputs
- Cash drawer monitoring
- Video loss and com activity LEDs for ease of installation and fault finding
- Host/PC programming




Function

CR-TEXT-340 is designed for single cash register applications on any BNC video surveillance systems. It captures and superimposes cash receipt transaction data onto live video with the cashier's activities recorded on the surveillance systems.

CR-TEXT-340 Implementing minimizes shrink and increases profits for F&B owners and retail managers. It is also capable of pinpointing flagged transactions such as VOID, REFUND, NO SALES etc : and compatible with most cash register and Point-Of-Sales Systems.

CR-TEXT-340 Customized PI4ECR printer interface boards and cables available for wide range of ECR and POS.

Connection



Specifications

MODEL	CR-TEXT-340
Hardware	
No. of Character	40 characters per line
No. of Line	10
No. of Digital Input	02 (two) dry contacts or TTL logic levels
No. of Digital Output	02 (two) open collector
Digital Output Sinking Current	200mA (max)
Video Input	1 Vpp, 75 ohm termination
Video Standard	2:1 interlace composite video (PAL or NTSC)
Communication Port	COM 1: compliant to EIA-232 standard, +/- 10V level COM2: selectable standard, EIA-232 or EIA-485 or TTL
Positioning of Displayed Text	Programmable
Sizes of Displayed Text	Programmable
Intensity of Text	Programmable
Text Scrolling Speed	Programmable
Flagged Transactions	16 (Sixteen) programmable
Displayed Text Background	On/Off/Transparent
Blinking Displayed Text	Yes, when received flagged transactions
Pausing of Displayed Text when Idle	Programmable
Transactions/Exceptions Logging Size	500, 1000, 2000 or 4000, optional
Real Time Clock/Time Stamp	Optional
Input Voltage	9 -12 Vdc
Reverse Voltage Protection	Yes, with diode protection
Input Current	200mA (typical)
Over Current Protection	Polyswitch fuse at 1.1A trip current
External Dimensions(mm)	98 (W) x 103 (L) x 28 (H)
Net Weight (kg)	0.55 approx.
Storage Temperature (deg°C)	-20.00 to 85.00
Operating Temperature (deg°C)	-10.00 to 55.00
Humidity	20.00 to 90.00 % RH (non-condensing)

社名 / 新光 株式会社

SK-COMPANY CO.,LTD

本社所在地 / 〒173-0032 東京都板橋区大山西町 2 - 3 SKビル 1F

TEL / +81-8032785551 FAX / +81-33972-0689

Distributor: