

EM Lock -600lbs Mortise Mount

Single Door Magnetic Lock With Mortise Mount & Signal Output



Features

- > Collinear Load Test 280kg,600pounds
- > Dual Voltage 12 or 24 VDC(optional)
- > The Standard Voltage is 12VDC when Finished
- > MOV Provides Reverse Current Protection
- > Anti-Residual Magnetism Designed
- > High Strength Material, Anodized Aluminum Housing
- > Design with no Mechanical Bolt
- > Increase the holding Force, Dual Insulative Hosing
- > CE Certificate by European Union, MA Certificate by China Public Security Office

Parameters

- > Lock Size: 231.6Lx41.6Wx24.5H(mm)
- > Armature plate: 180Lx38Wx11H(mm)
- > Holding Force: 280kg(600Lbs)
- > Voltage: 12/24VDC+10%
- > Current Draw: 12V/500mA 24V/250mA
- > Suitable for: Wooden door , Glass door ,Metal door , Fireproof door
- > Signal Output: Need to order YM-280M-S
- > Surface Temp: $\leq +20^{\circ}\text{C}$
- > Operating Temp: 10~+55°C(14-131F)
- > Suitable Humidity: 0~90%(non-condensing)
- > Finishes for Shell: Anodized aluminum
- > Finishes for Magnetic: Zinc
- > Finishes for Armature: Zinc
- > Weight: 2kg