


# ITK-ITO2000A-2-ITH1550CHW-2

## IP 2-Wire Kit



### Features

- HD CMOS camera
- 7-inch capacitive touch screen, resolution 800×480
- IPC surveillance (VTNC3000A needed)
- Alarm integration
- 2-Door control
- Remote intercom with mobile APP (VTNC3000A needed)



### Technical Specification

#### Video Outdoor Station

Model	ITO2000A-2
-------	------------

#### System

Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS

#### Video

Video Compression	H.264
Image Sensor	1/3" 1.3MP CMOS
Lens	2.8mm
Angle of View	D:120° H:90°
Day/Night	Color Image

#### Audio

Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk

#### Operation Mode

Keypad	Single Mechanical Button
--------	--------------------------

#### Interface

Door Control	2(1 relay out for main lock, 1 extended by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1

#### Network

Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP

#### General

Ingress Protection	IP54,IK07
Tamper Switch	1
Installation	Surface & Flush
Material	Stainless steel
Power	DC 24V or supply directly by VTNC3000A
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	-40°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	129.9mm×32.2mm×140mm
Weight	0.8Kg

#### Video Indoor Monitor

Model	ITH1550CHW-2
-------	--------------

#### System

Main Processor	Embedded Micro Process
Operation System	Embedded LINUX OS

#### Video

Video Compression	H.264
-------------------	-------

#### Audio

Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk

#### Display

LCD Screen	7" 800x480, Capacitive
------------	------------------------

## Operation Mode

Input	Touch buttons
-------	---------------

## Interface

Alarm In	6
----------	---

Alarm Out	1
-----------	---

RS485	1
-------	---

## Network

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------

## General

Memory Slot	Micro SD, Max 32G
-------------	-------------------

Installation	Surface
--------------	---------

Power	DC 24V
-------	--------

Power Consumption	Standby $\leq 1.5W$ , work $\leq 7W$
-------------------	--------------------------------------

Working Temperature	-10°C~+55°C
---------------------	-------------

Relative Humidity	10%~90%RH
-------------------	-----------

Dimensions	200.5mm×136.5mm×22.0mm
------------	------------------------

Weight	0.8Kg
--------	-------

## Application

