

01 Methods of Entry



User Access Code
Support user access codes (5-12 digit numbers)



Smart Card
RFID card or other smart card (Mifare can be used for the access)



Key Tag
Place the key tag on the card reader

02 Enhanced Features

Digital Touch Pad Screen

Gently touch the 'Touch Pad Screen' to activate

Slim and sleek style

unique look and exclusive design raise the standard of how a door lock should look and feel

Anti-panic exit system

allows you to open the door by simply turning its handle from inside

Electrostatic Discharge (ESD) prevention

uses a circuit technology that can withstand high voltage electrostatic shocks to enhance stability

Locking mode (manual/automatic)

Burglar alarm & Fire detection sensor

'Do not disturb' mode

ensures security of not being disturbed from the outside

PSB fire tested

External power source connector

Mechanical override key (emergency)



03 Specifications

Section	
Key Type	Smart Card(13.56MHz RF chip/A Type) & Key Tag
User Capacity	20 (user access code, card, key tag)
User Access Code	5-12 Digits number combination
Product size	Outer body : 82x299x118mm (WxMxD) Inner body : 79x290x80.3mm (WxMxD)
Material	Zinc, Aluminium and ABS plastic
Door Thickness	Applicable 40-60mm (Max. 80mm, Option)
Humidity	20-80%
Power	DC 6V (AA Alkaline batteries, 8pcs)
Battery Lifetime	Approximately 12 months (average - 10 times per day)