

AC-3008

Metal waterproof access control system

Product features

- ♦ Working voltage DC/AC9V-28V
- ◆Waterproof degree: IP68
- ◆With Anti-theft alarm output for external alarm device.
- ◆With bult-in anti-theft equipments.
- ◆Support enrolling cards continuously
- ◆Perfect disign, with backlight and fashion silver finish.
- ◆Waterproof design for outdoor use.
- ♦ strong standalone function device, can be used as WG26 reader alone.
- ◆Capacity:2000 user's cards,2000 codes;
- ◆Access ways : cards ,code,card +code.
- ◆Low power:static current less than 30mA.
- ◆Support only keypad
- •users can reset private passwords.
- ◆Search fast less than 0.1s.
- ♦ Wiegand output W26 for card and W4 for codes.
- ◆use keypad to delete lost cards for safety.
- ◆Short-circuit protect : when relay or alarm output short circuit, it will shut up output in 100 µ S.

Technical parameters

Environment Temperature: $-45\%\sim60\%$ Environment Humidity: $10\%\sim90\%$ Electric lock output: $\leqslant 3A$ Alarm output: $\leqslant 20A$ Output short-coult protection time: $\leqslant 100\mu \rm SS$ Open-door time: $0\sim99$ seconds (adjustable) Size: 120 *80*25mm

Products types

Card style	frequency	Reading range
EM	125KHz	5-15CM
HID	125KHz	5-15CM
MIFARE	13.56MHz	3-10CM





Tel: +65 6748 1155







Stereo effect