

EM Lock – 600Lbs

Single Door Magnetic Lock With LED (600Lbs)



Features

- > Collinear Load Test 280kg, 600pounds
- > Dual Voltage 12 or 24 VDC (optional)
- > The Standard Voltage is 12VDC when Finished
- > MOV Provides Reverse Current Protection
- > Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- > LED Indicates the Door Status
- > Door Status sensor (NO/NC/COM)
- > Anti-Residual Magnetism Designed
- > High Strength Material, Anodized Aluminum Housing
- > Design with no Mechanical Bolt
- > Increase the holding Force, Dual Insulative Housing
- > CE Certificate by European Union, MA Certificate by China Public Security Office

Parameters

- > Lock Size: 250Lx48.5Wx25H(mm)
- > Armature plate: 180Lx38Wx11H(mm)
- > Holding Force: 280kg(600Lbs)
- > Voltage: 12/24VDC+10%
- > Current Draw: 12V/500mA 24V/250mA
- > Optional Bracket: AB-280UL AB-280L AB-280ZL
- > Signal Output: Dry Contact, Max Rating of Contact Current 3A
- > LED indicates the door is unlock, Green indicates the door is lock
- > Suitable for: Wooden door , Glass door ,Metal door , Fireproof door
- > Surface Temp: $\leq +20^{\circ}\text{C}$
- > Operating Temp: $10\sim +55^{\circ}\text{C}$ (14-131F)
- > Suitable Humidity: 0~90% (non-condensing)
- > Finishes for Shell: Anodized aluminum
- > Finishes for Magnetic: Zinc
- > Finishes for Armature: Zinc
- > Weight: 2kg