

Electric Bolt

Fail Safe Electric Bolt With Magnetic



Features

- > The Photoelectricity Controls Technology, Prevent the Trouble of the Machinery
- > Low Temperature, safe & Durable; Low Power, Environmental Protection
- > Special Designed Solenoid for Strength and Long Life with 500000 Operations
- > MOV Provides Reverse Current Protection
- > The Intelligent form Jing Piece is Disposed, Three Magnitudes of Electric Current are Used
- > Superior Strength Aluminum Alloy, Solid Stainless Steel Bolt, Suitable for all Kind of the Door
- > CE Certificate by European Union, MA China Public Security office, Photoelectricity Control, Low Temperature
- > A: The Low Electric Current is Changed in the Twinkling of and Eye;
- > B: Location on the Door is not Straight, The Door withstands the bolt, The Temperature will be low;
- > C: The Photoelectricity Controls Technology, Prevent the Trouble of the Machinery.

Parameters

- > Fail Safe: Locked when energized, Face Plate: 205Lx35WX41H(mm)
- > Strike: 90Lx25Wx2H(mm), Bolt: 16mmDIA, stainless steel 16mm throw
- > Voltage: DC12V, Start Current: 900Ma, Standby Current: 150mA
- > Solid Bolt: polishing housing, 800Kg Holding Force
- > Suitable For: Wooden Door, Glass Door, Metal Door
- > Autolock Time Delay: 0,3,6,9sec.
- > Signal Output: Door status Output, NC/COM
- > Surface Temp: Low Temperature
- > Induction Distance: 8mm
- > Operating temp: -10~+25°C (14-131F)
- > Operating Humidity: 0~90%(non-condensing)
- > Special Designed: Tested to 500000 cycles
- > Face place material: High Aluminum, Carrulous Line Finished
- > Optional Bracket: AB-600 AB-601 AB-500 AB-700 Weight:
- > 0.7kg