

WD-605 Fire Door Holder

Floor and Wall Mount Door Holder



Features

- > Collinear Load Test 50kg, 100pounds
- > Dual Voltage 12 or 24 VDC (optional)
- > The Standard Voltage is 12VDC when Finished
- > MOV Provides Reverse Current Protection
- > Low Power, Environmental Protection
- > Anti-Residual Magnetism Designed
- > Professional Design, Dual Insulative Housing
- > Shunt and Defend the Cigarette Door Automatically During the Fire Alarm
- > With the Hand Moves and Closes the Door to Release the Button
- > CE Certificate by European Union

Parameters

- > Dimensions: 118Lx92Wx120H(mm)
- > Holding Force: 50kg (100Lbs)
- > Voltage: 12/24VDC+10%
- > Current Draw: 12V/100mA 24V/50mA
- > Optional: The Hand Moves and Closes the Door to Release the Button
- > Suitable for: All Kind of the Single & Double Smoke proof Door
- > Surface Temp: $\leq +20^{\circ}\text{C}$
- > Operating Temp: $-10\sim +55^{\circ}\text{C}$ (14-131F)
- > Suitable Humidity: 0~90%(non-condensing)
- > Finishes for Shell: High Temperature Paint and Environmental Protection Zinc
- > Finishes for Armature: Zinc
- > Weight: 0.96kg