

# ITK-ITO2111D-WP-ITH5221D

## Wi-Fi Kit



### Technical Specification

#### Video Outdoor Station

Model	ITO2111D-WP
-------	-------------

#### System

Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS

#### Video

Video Compression	H.264
Image Sensor	1/4" 1MP CMOS
Lens	2.2mm
Angle of View	D:125° H:105°
Day/Night	ICR

#### Audio

Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk

#### Operation Mode

Keypad	Single Mechanical Button
--------	--------------------------

#### Interface


Door Control	2(1 relay out for main lock, 1 extended by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1

#### Network

Wi-Fi	IEEE802.11b/g
Ethernet	10M/100Mbps Self-adaptive

### Features

- 7-inch capacitive touch screen, resolution 1024×600
- IPC surveillance
- Alarm integration
- 2-Door control
- Wi-Fi & POE
- Remote intercom with mobile APP



Network Protocol	TCP/IP
------------------	--------

#### General

Ingress Protection	IP65,IK07
Tamper Switch	1
Memory Slot	Micro SD, Max 32G
Installation	Surface
Material	Plastic
Power	DC 12V, PoE(802.3af)
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	-30°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	135mm×70.4mm×34.4mm
Weight	0.4Kg

#### Video Indoor Monitor

Model	ITH5221D
-------	----------

#### System

Main Processor	Embedded Micro Process
Operation System	Embedded LINUX OS

#### Video

Video Compression	H.264
-------------------	-------

#### Audio

Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk

## Display

LCD Screen	7"1024x600, Capacitive
------------	------------------------

## Operation Mode

Input	Touch buttons
-------	---------------

## Interface

Alarm In	6
----------	---

Alarm Out	1
-----------	---

RS485	1
-------	---

## Network

Wi-Fi	IEEE802.11b/g
-------	---------------

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------

## General

Memory Slot	Micro SD, Max 32G
-------------	-------------------

Installation	Surface
--------------	---------

Power	DC 12V, PoE(802.3af)
-------	----------------------

Power Consumption	Standby ≤1W, works≤7W
-------------------	-----------------------

Working Temperature	-10°C~+55°C
---------------------	-------------

Relative Humidity	10%~90%RH
-------------------	-----------

Dimensions	215.0mm×140.0mm×21.0mm
------------	------------------------

Weight	0.8kg
--------	-------

## Application

